

Item	Pet Name	SyncMaster 1100DF
	Model Name	CF21GS (21", DynaFlat, 0kHz)
CDT	Size	21" (20" Viewable)
	Face	DynaFlat
	Deflection	90 Degrees
	Pitch	0.20(H) mm
	Surface treatment	Multi-Layer Coating
Input Signal	Video signal	RGB Analog
	Sync signal	Separate H/V, Composite, SOG
	Horizontal Frequency	30-121 kHz
	Vertical Frequency	50-160 Hz
	Pixel Frequency	340 MHz
	Signal Connection	15pin D-Sub+BNC
Resolution	Max	2048x1536 @75Hz
	VESA	1920x1440 @80Hz 1800x1440 @80Hz 1856x1392 @82Hz 1792x1344 @85Hz 1600x1200 @95Hz 1280x1024 @110Hz 1152x864 @129Hz 1024x768 @144Hz 800x600 @160Hz 640x480 @160Hz
	Recommended	1,280x1,024 @85Hz
Display Size	Typical(mm)	393x295
	Max(mm)	406.4x304.8
Mode	Factory/User	8/10 modes
Power	Supply	AC90~264VAC,50/60Hz
	Consumption(nominal)	120WW
	Power Management	<2W @Off State
	Regulation	EPA/Energy2000/VESA DPMS
User Control	Display Director™	Brightness, Contrast, Position, Size, Zoom, Parallelogram, Rotation, Pincushion, Trapezoid, Pinbalance, Side Pin Corner, Pin balance Corner, Color1/2, sRGB, Clear Moire, Linearity, Focus, Convergence, Purity Degauss, Recall, Video Input level, Sync. Input type, D-sub/BNC, Display Timing, Menu Position, Menu Duration, Languages, OSD Lock/Unlock, Highlight Zone(Position, Size, Contrast, Color, Zoom, Sharpness)
	OSD Languages	Applied
Plug & Play	DDC	DDC 2B/2Bi/GTF
Special Feature		Highlight Zone II™, MouScreen™
Regulation	Enviromental/ Ergonomics	UL, CSA, TUV, CB, NEMKO, Korea EK, CCIB, PSB, NOM, GOST
	Windows Logo	Windows98/2000/ME/XP
Set Size	Set(WxDxH mm)	504x500x508
Weight	Set/Packing (Kg)	28/32.1
Accessory	Software Kit	Install Driver, Manual, Natural Color™