

## 2. Specifications

		ML-1210 (ML-1220M)	ML-1250
<b>Engine</b>	Speed	12ppm	
	Resolution	600 x 600 dpi	1200 x 600 dpi
	FROP(First Power On Time)	Under 12.5 sec	
	Warm-Up Time	30 sec	
	Power Consumption	25W (Print), 10W (Sleep)	
	Dimension	329 x 355 x 231 mm (13" x 14" x 9.1")	
	Weight	Max 6.5Kg (With Toner Cartridge)	
<b>Controller</b>	Processor	Jupiter 366MHz	61200 66MHz
	Memory	8MB Equivalent	4MB
	Emulation	SmartGDI	PCL6
	Interface	IEEE1284, USB (ML-1220M : USB ONLY)	
	OS Support	Windows 95/98/2000/Me/NT, Linux(Radhat 6.0), iMac(Mac OS 8.0)	
	N/W	External	
<b>Paper</b>	Input	150 sheets	
	Output	100 sheets	
	Manual	1 sheet	
	Media Type	A4, Letter, Legal, Executive, B5, A5, Folio, 7 3/4(Monarch), #10, DL, C5, C6, B5	
<b>Toner</b>	Type	Single Cartridge	
	Life	2,500 sheets	
	Cartridge	2,500 (Initial : 1,000)	
	Pick up Roller	60,000	
	Feed Roller	60,000	
	Transfer Roller	60,000	
	Fuser	40,000	
<b>User interface</b>	Key & LED	3Key, 4LEDs	
	LCD	No	
	Toner Save	YES	
	Reprint	YES	